

### **DECLARATION OF PERFORMANCE**

# According to Construction Products Regulation EU N° 305/2011 N° 0832-CPD-0374

Product Name:	YBO-BS, YBO-BS(WHT) & YBO-BS(HFP)	
Intended use:	Intelligent analogue addressable loop powered base sounder for use in fire detection and alarm systems for buildings	
Manufactured by:	Hochiki Europe (UK) Ltd, Grosvenor Road, Gillingham, Kent, ME8 0SA	
Authorised representative:	N/A	
System of Assessment:	System 1	
Assessed by:	BRE Global Limited (Notified Body 0832) has performed type testing of the product, initial inspection of the manufacturing plant and of factory production control with continuous surveillance, assessment and evaluation of factory production control under system 1 and issued following certificate of conformity:  0832 - CPD - 0374	
Declared performance:	All requirements including all essential characteristics <sup>(1)</sup> and corresponding performances <sup>(2)</sup> as described in the harmonised standards:  EN54-3:2001 Fire detection and fire alarm systems - Part 3:  Fire alarm devices - Sounders  for the intended uses indicated above have been determined.  (1) See Annex A for the Essential Characteristics details (2) See Annex B for additional performance details	
	tioned products are in conformity with the performance and essential characteristics s declaration of performance is issued under the sole responsibility of Hochiki Europe (UK	
Signed for and on behalf of the mar	nufacturer by:	
	Date of issue 27 <sup>th</sup> June 2013	
Ray Turner Compliance Manager		

Page 1 of 3

HOCHIKI EUROPE (UK) LIMITED
Grosvenor Road, Gillingham Business Park,
Gillingham, Kent, ME8 0SA, United Kingdom
Telephone: +44 (0)1634 260133
Facsimile: +44 (0)1634 260132
e-mail (UK Sales): sales@hochikieurope.com e-mail (Non UK Sales): export@hochikieurope.com www.hochikieurope.com

Reg. Address: 11 Raven Wharf, Lafone Street, Butlers Wharf, London SE1 2LR Registered in England no. 2639909 VAT no. GB 573 8188 03















### Annex A - Essential Characteristics

Essential characteristics	EN54-3:2001 +A1:2002 + A2:2006	Performance
Performance under fire conditions	4.2, 4.3, 5.2, 5.3	Pass
Operational reliability	4.4, 4.5, 4.6, 5.4	Pass
Durability of operational reliability: Temperature resistance	5.5, 5.6 <sup>a</sup> , 5.7, 5.8, 5.9	Pass
Durability of operational reliability: humidity resistance	5.8, 5.9, 5.10 <sup>a</sup>	Pass
Durability of operational reliability: corrosion resistance	5.11	Pass
Durability of operational reliability: shock and vibration resistance	5.12 to 5.15	Pass
Durability of operational reliability: electrical stability	5.16	Pass
Durability of operational reliability: resistance to ingress	5.17	Pass

a outdoor devices only

HOCHIKI EUROPE (UK) LIMITED
Grosvenor Road, Gillingham Business Park,
Gillingham, Kent, ME8 0SA, United Kingdom
Telephone: +44 (0)1634 260133
Facsimile: +44 (0)1634 260132
e-mail (UK Sales): sales@hochikieurope.com e-mail (Non UK Sales): export@hochikieurope.com www.hochikieurope.com

Reg. Address: 11 Raven Wharf, Lafone Street, Butlers Wharf, London SE1 2LR Registered in England no. 2639909 VAT no. GB 573 8188 03













Page 2 of 3



## Annex B – Additional Performance Details Approved tones:

27 – 660 Hz : 6500 ms / Off : 13000 ms	
28 – 660 Hz Continuous	
29 – 554 Hz : 500 ms / 440 Hz : 500 ms	
30 – 660 Hz : 500 ms / Off : 500 ms	
31 – 2850 Hz : 150 ms / Off : 100 ms	
32 – Sweep 2400 Hz – 2850 Hz over 20 ms (50 Hz)	
33 – Sweep 800 Hz – 970 Hz over 500 ms (2 Hz)	
34 – 988 Hz : 250 ms / 645 Hz : 250 ms	
35 – 510 Hz : 250 ms / 610 Hz : 250 ms	
36 – Sweep 800 Hz – 970 Hz over 110 ms (9 Hz)	
37 – Sweep 800 Hz – 970 Hz over 330 ms (3 Hz)	
38 – 845 Hz Continuous 39 – 970 Hz : 1000 ms / Off : 1000 ms	
41 – Sweep 2400 Hz – 2850 Hz over 110 ms (9 Hz)	
42 – Sweep 2400 Hz – 2850 Hz over 330 ms (3 Hz)	
43 – 2850 Hz : 1000 ms / Off : 1000 ms	
44 – 2400 Hz : 150 ms / 2850 Hz : 150 ms	
45 – (German) Whoop 1200 Hz – 500 Hz : 1000 ms / Off : 10 ms	
46 – 440 Hz : 600 ms / Off : 600 ms	
47 – Whoop 500 Hz – 1200 Hz : 3750 ms / Off : 250 ms	
48 – ISO8201 : 925 Hz, 628 Hz : 250 ms / Off : 500 ms	
49 – ISO8201 : Sweep 300 Hz – 1200 Hz : 500 ms / Off : 500 ms	
50 – ISO8201 : Sweep 1200 Hz – 300 Hz : 500 ms / Off : 500 ms	
51 – Whoop 500-1200 3500 ms /Off 500 ms	

Page 3 of 3

HOCHIKI EUROPE (UK) LIMITED
Grosvenor Road, Gillingham Business Park,
Gillingham, Kent, ME8 0SA, United Kingdom
Telephone: +44 (0)1634 260133
Facsimile: +44 (0)1634 260132
e-mail (UK Sales): sales@hochikieurope.com e-mail (Non UK Sales): export@hochikieurope.com www.hochikieurope.com

Reg. Address: 11 Raven Wharf, Lafone Street, Butlers Wharf, London SE1 2LR Registered in England no. 2639909 VAT no. GB 573 8188 03











