

Product Name

R
(Linear)

Technical description

Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket and goniometer in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic in optical PC.

Supply

Drivers included and integrated.
Voltage 230V AC 50Hz.
Temperature -40° +45°

Installation

Wall and ceiling.

Applications

Churches, Museums, Shop windows, Facades decoration, Fair exhibitions

Size (mm)



250 x 176 x 42,6

Colour

Dark grey 4

Decay of the luminous flux

≥50.000 hr L80B20



2,1 Kg

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L000R40H9LI40050	LED	50 W	5622 lm	8150 lm	4000 K	>80	H9	Dark grey	-

Accessories

Cable with connector
Ca. 2m/Co. IP 2 poli
LKITA00000000040
Ca. 2m/Co. IP 3 poli
LKITA00000000041

Ceiling Kit
LKITA00000000060
Galvanised iron
LKITA00000000061
Inox

Pole connection A
Max 4 x R
LKITA00000040001

Fast connector
IP 2 poles
LKITA00000000017

Fast connector
IP 3 poles
LKITA00000000003

Pole mounting
LKITA00000000002

LANZINI indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.