

Product Name

Qm

(Linear)

Technical description

Adjustable floodlight suitable for wall or ceiling application, designed to produce direct or indirect light. It has a low visual impact. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted with polyester powder. Supplied with a painted galvanised steel bracket. Screws made of AISI 304 stainless steel. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.

Supply

Driver included and integrated linear
Input voltage 230 V AC 50Hz.
Temperature -40° +45°

Installation

Wall and ceiling

Applications

Big boards, shop window, facades decoration

Size (mm)




211 x 233 x 37

Colour

Dark grey **4**

Decay of the luminous flux

≤50.000 hr L80B20



IP66

IK08



1,2 Kg

Low Flicker



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00QM4060LI40045	LED	45 W	4510 lm	7065 lm	4000 K	>80	60°	Dark grey	

Accessories



Pole connection B
Max 2 x Qm
LKITA00000040002



Fast connector
IP 3 poles
LKITA00000000003

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.