

## Product Name

Q

(External driver)

## Technical description

Essential and clean design for a floodlight which becomes the main protagonist of the space through a confident style. Supplied with bracket and goniometer, Q can be oriented in multiple directions, thus creating lighting directions always different, both for wall (standard bracket) and ceiling application (optional bracket). Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Tempered glass sodium-calcium type, 5 mm thickness. 91% transparency is guaranteed. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic optical PC.

## Supply

External driver (also in versions dimmable or DALI)  
Input voltage 220 - 240V AC 50/60Hz.  
Temperature -40° +45°

## Installation

Wall and ceiling

## Applications

Facades decoration, Commercial areas, Parking, Fair exhibitions, Advertising installations

## Size (mm)

220 x 270 x 96

## Colour

Dark grey **4**

## Decay of the luminous flux

≥100.000 hr L80B20



Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
<b>L000Q40A2BL40100</b>	LED	100 W	11553 lm	16800 lm	4000 K	>80	ASIM 55°	Dark grey	-
<b>L000Q40A2DI40100</b>	LED	100 W	11553 lm	16800 lm	4000 K	>80	ASIM 55°	Dark grey	Dimmer
<b>L000Q40A2DA40100</b>	LED	100 W	11553 lm	16800 lm	4000 K	>80	ASIM 55°	Dark grey	DALI

## Accessories



Pole connection A  
Max 4 x Q  
LKITA00000040001



Fast connector  
IP 2 poles  
LKITA00000000017



Fast connector  
IP 3 poles  
LKITA00000000003



Ceiling Kit  
LKITA00000000060  
Galvanised iron  
LKITA00000000061  
Inox



Cable with connector  
Ca. 2 m., Con 2 poles  
LKITA00000000040  
Ca. 2 m., Con 3 poles  
LKITA00000000041



Pole mounting  
bracket  
LKITA00000000002

