

Product Name

Q2

(External driver)

Technical description

Q2 is an innovative and functional LED product with an industrial appeal, suitable for both indoor and outdoor illumination. It has been developed to satisfy the needs of commercial and industrial areas at their best. Body in die-cast aluminum alloy UNI EN 1706 (Low copper content) painted polyester powder. Supplied with a painted galvanised steel bracket and goniometer in technopolymer with anti-rotation block in die-cast aluminum and powder painted. Stainless steel screws AISI 304. Tempered glass sodium-calcium type, 5 mm thickness. 91% transparency is guaranteed. Silicone gaskets. LED light source (lumileds), colour temperature (4000 K Neutral White). High coefficient of performance chromatic CRI>80. Optic in optical PC.

Supply

External driver in ON-OFF, dimmable or DALI.
Voltage 220-240V AC 50/60Hz.
Temperature -40° +45°

Installation

Wall, ceiling and suspended.

Applications

Commercial areas, Industrial areas, Warehouses, Production areas, Sport facilities

Size (mm)



466 x 251 x 101

Colour

Dark grey 4

Decay of the luminous flux

≥100.000 hr L80B20



IP66

IK08

RG0
IEC 62471

RG1
IEC 62778

U.V.

7,5 Kg

Low Flicker
≤3%

RoHS

LED

05

Code	Source	Power	Lm (Output)	Lm (Tc=25°)	Temperature	CRI	Beams	Colour	Control
L00Q240A2BL40170	LED	170 W	19640 lm	28560 lm	4000 K	>80	ASIM 55°	Dark grey	-
L00Q240A2DI40170	LED	170 W	19640 lm	28560 lm	4000 K	>80	ASIM 55°	Dark grey	Dimmer
L00Q240A2DA40170	LED	170 W	19640 lm	28560 lm	4000 K	>80	ASIM 55°	Dark grey	DALI

Accessories

Suspension Kit
LKITA00000000004

Modules assembly kit
LKITA00000000005

Fast connector
IP 2 poles
LKITA00000000017

Fast connector
IP 3 poles
LKITA00000000003

Bracket Kit
Galvanised iron
LKITA00000000043

Inox
LKITA00000000044

Cable with connector
Ca. 2 m., Con 2 poles
LKITA00000000040

Ca. 2 m., Con 3 poles
LKITA00000000041

Pole mounting bracket
LKITA00000000002

90° Bracket kit
LKITA00000000020

Grid kit
IK10 protection
LKITA00000000039

Lanzini indicates the luminous flux of the luminaire in the catalogs with a tolerance of ± 10% respect to the indicated value. The total W indicates the total power absorbed by the LED + power supply system that does not exceed 10% of the indicated value.